



Keg River Chemical Corp.
10350 – 21 Street
Edmonton, AB Canada T6P 1W4
Tel: (780) 417-2463
Fax: (780) 416-0843

**MATERIAL SAFETY DATA SHEET
FOR NUTRASUL 90 SULFUR FERTILIZER**

A. GENERAL INFORMATION

December 2010

Trade Name (Common Name of Synonym) – **NutraSul 90% Sulfur Fertilizer (KEG RIVER BRAND)**

Formula: 90% Sulfur (CAS.No. 7704-34-9) Molecular Weight: N/A
10% Bentonite Clay

B. TRANSPORTATION REQUIREMENTS (Non Regulated as per following exemptions/provisions, and observations):

US and Canadian Shipments: non regulated as per T.D.G.A.R.'s exemption part 2.3 (a) (xxxviii) and 49 CFR (Canadian Shipments and Packaging 171.12 (a) and CFR 49 (Special Provisions 172.102 pt 30.)

International Shipments:

AIR (IATA): Exempted under Special Provision A 105 SEA (IMDG): Exempted as per Sulfur Observations Part 1 & 2

Appearance: Specifically formed product in the shape of pastilles.

TRANSPORTATION EMERGENCIES: call collect CANUTEX 613-996-6666 (24 hours).

WHIMIS: non-controlled product in accordance with sub-paragraph 13(a)(i-iv) or paragraph 14 (a) of the Hazardous Products Act.

C. FIRST AID MEASURES

Skin: Wash with mild soap and water.

Eyes: Irrigate thoroughly with copious quantities of plain water.
Inadequate irrigation may increase the irritation. Do not use Boric Acid.

D. HAZARDS INFORMATION

Inhalation: Sulfur dust may irritate the mucous membranes of the respiratory passages.

Ingestion: Solid Sulfur is virtually non-toxic. It can be taken internally in fairly large doses without injury.

Skin: In some individuals, Sulfur dust has an irritant action, which may be aggravated by perspiration or moisture.

Eyes: Sulfur dust is capable of irritating the inner surfaces of the eyelids.

Permissible Concentration: None established. Unusual Chronic Toxicity: N/A

Flash Point °C	Auto Ignition °C	Flammable Limits in air
Pure Liquid S – 188 °C, (370°F)	Dust clouds 190 °C (374 °F)	Minimum explosion concentration is approximately 55 gm per cu. Meter (0.0549 oz per cu. ft). Maximum explosive concentration lies between 1000 and 2000 gm/m ³ probably about 1400 gm/m ³ .
Impure Liquid S - 168 °C, (335 °F)	Undispersed dust, 220 °C, (428 °F)	

Unusual Fire and Explosion Hazards: Dust suspended in air is readily ignited by flame, static electricity or friction spark. Every reasonable step must be taken to minimize dust formation. Dust tight casings should be equipped with explosion relief vents. Sparkless electric equipment is recommended. Handling equipment must be grounded or bonded to avoid static electricity. Keep away from sources of flame or sparks. Detailed recommendations in Manufacturing Chemists Association SD-74 and National Safety Council 612 Bulletins covering "Sulfur" should be followed when handling sulfur fertilizers.

Explosive Limits: LEL 55 gm/m³
UEL 1400 gm/m³

Resistivity: Measures the tendency to build up electrostatic charges in airborne dust near stored Sulfur. With increased Bentonite content, airborne dust conductivity improves and electrostatic charges bleed off more readily.

Resistivity: 10.0 x 10⁹ ohm-cm

E. PRECAUTIONS/PROCEDURES

◆ Fire Extinguishing Agents Recommended:

1. A fine water spray or fog is recommended.
2. CO₂ or dry chemical.
3. Small fires may be smothered with sand or solid Sulfur.

◆ Fire Extinguishing Agents to Avoid:

Hoses and extinguishers with pressure streams should be avoided where solid Sulfur is dusty or where it may create a further hazard by raising more dust clouds.

◆ Special Fire Fighting Precautions:

Because burning Sulfur evolves Sulfur dioxide, breathing apparatus or gas masks approved for use in acid-gas atmosphere should be used. Fumes from unprotected Sulfur fires shall be avoided, if possible, by approaching for the upwind side.

◆ Ventilation:

Local exhaust if dusty conditions prevail.

◆ Normal Handling:

Avoid breathing dust and keep clothing as free from dust as possible.

◆ Storage:

Solid becomes corrosive to metals when stored wet. Sulfur/Bentonite fertilizer will physically break down when exposed to moisture or water.

◆ Spill or Leak:

Shovel into disposal containers or cover with tarp. For landfill disposal, mix with limestone 3 times the weight of Sulfur.

◆ Special: Precautions/Procedures/Label Instructions:

Eye Wash equipment near the work area.

F. PERSONAL PROTECTIVE EQUIPMENT

◆ Respiratory Protection:

Dust-type respirators shall be provided for dusty conditions. Breathing apparatus must be available for emergency use in case of fire.

◆ Eyes and Face:

Dust-tight goggles with plastic or rubber frames may be helpful in dusty conditions.

◆ Hands, Arms and Body:

Workers whose skin may be sensitive to Sulfur dust should button collars, roll sleeves down, and gather trousers at the ankle. Gloves may be helpful.

◆ Other Clothing and Equipment:

Hardhat and safety shoes. Fire-retardant fabric is recommended. Sulfur impregnated clothing should not be worn.

G. PHYSICAL DATA

Material is (at normal conditions) __Liquid <input checked="" type="checkbox"/> Solid __Gas		Appearance and Odour Green / Earth tone colours. May have slight Sulfur odour. Pastille in shape.	
Boiling Point 444 °C (832 °F)	Specific Gravity Solid, 2.07/gm/ml	Vapour Density > 1	Melting Point 119 °C (246 °F)
Solubility in Water (% by weight) Insoluble	pH Neutral when dry	Vapour Pressure (mm Hg at 20 °C) Solid: Less than 0.0001 mm. Hg at 20 °C (68 °F).	
Evaporation Rate (Butyl Acetate =)(Ether =) N/A		% Volatiles by Volume N/A	

H. REACTIVITY DATA

Stability

__ Unstable Stable

Conditions to Avoid

The main hazards are fire and dust explosions.

Hazardous Polymerization conditions to Avoid.

__ May Occur Will not occur.

I. HAZARDOUS INGREDIENTS (Mixtures Only)

◆ Material or Components:

Mixtures with chlorates, nitrates or other oxidizing agents may be explosive. Sulfur will react with alkalis or alkaline earths.

NOTICE:

The data and information presented herein are based upon tests, research and reports, which are considered by us to be reliable, and believed to be accurate. The data and information are presented without warranty, guarantee or liability on our part, and are presented to the customer for his own consideration, investigation and verification.